

配管用ステンレス鋼管の寸法 JISG3459

単位 (mm)

呼び径		外径 mm	呼び厚さ						
A	B		Sch5	Sch10	Sch20	Sch40	Sch80	Sch120	Sch160
6	1/8	10.5	1.0	1.2	1.5	1.7	2.4		
8	1/4	13.8	1.2	1.65	2.0	2.2	3.0		
10	3/8	17.3	1.2	1.65	2.0	2.3	3.2		
15	1/2	21.7	1.65	2.1	2.5	2.8	3.7		4.7
20	3/4	27.2	1.65	2.1	2.5	2.9	3.9		5.5
25	1	34.0	1.65	2.8	3.0	3.4	4.5		6.4
32	1 1/4	42.7	1.65	2.8	3.0	3.6	4.9		6.4
40	1 1/2	48.6	1.65	2.8	3.0	3.7	5.1		7.1
50	2	60.5	1.65	2.8	3.5	3.9	5.5		8.7
65	2 1/2	76.3	2.1	3.0	3.5	5.2	7.0		9.5
80	3	89.1	2.1	3.0	4.0	5.5	7.6		11.1
90	3 1/2	101.6	2.1	3.1	4.0	5.7	8.1		12.7
100	4	114.3	2.1	3.1	4.0	6.0	8.6	11.1	13.5
125	5	139.8	2.8	3.4	5.0	6.6	9.5	12.7	15.9
150	6	165.2	2.8	3.4	5.0	7.1	11.0	14.3	18.2
200	8	216.3	2.8	4.0	6.5	8.2	12.7	18.2	23.0
250	10	267.4	3.4	4.0	6.5	9.3	15.1	21.4	28.6
300	12	318.5	4.0	4.5	6.5	10.3	17.4	25.4	33.3
350	14	355.6	4.5	5.0	8.0	11.1	19.0	27.8	35.7
400	16	406.4	4.5	5.0	8.0	12.7	21.4	30.9	40.5
450	18	457.2	4.5	5.0	8.0	14.3	23.8	34.9	45.2
500	20	508.0	5.0	5.5	9.5	15.1	26.2	38.1	50.0
550	22	558.8	5.0	5.5	9.5	15.9	28.6	41.3	54.0
600	24	609.6	5.5	6.5	9.5	17.5	31.0	46.0	59.5
650	26	660.4	5.5	8.0	12.7	—	34.0	49.1	64.2
700	28	711.2	5.5	8.0	12.7	17.5	—	—	—
750	30	762.0	—	8.0	12.7	17.5	—	—	—
800	32	812.8	—	8.0	12.7	17.5	—	—	—
850	34	863.6	—	8.0	12.7	17.5	—	—	—
900	36	914.4	—	8.0	12.7	19.1	—	—	—
1000	40	1016.0	—	9.5	14.3	26.2	—	—	—